

GL Silicon N-Channel Super-Junction Power MOSFET

General Description:

GL20J80A0 the silicon N-channel Enhanced VDMOSFETS, is obtained by the self-aligned Super-junction Technology which reduce the conduction loss, improve switching performance and enhance the avalanche energy. The transistor can be used in various power switching circuit for system miniaturization and higher efficiency. The package form is TO-263, which accords with the RoHS standard.

Features:

- Fast Switching
- Low Gate Charge and Rdson
- Low Reverse transfer capacitances
- 100% Single Pulse avalanche energy Test

Applications:

- Switch Mode Power Supply(SMPS)
- Uninterruptible Power Supply(UPS)
- Power Factor Correction(PFC)

Absolute (Tc= 25°C unless otherwise specified):



Symbol	Parameter	Rating	Units
V_{DSS}	Drain-to-Source Voltage	800	V
I_D	Continuous Drain Current	20	A
I_{DM}^{a1}	Pulsed Drain Current	80	A
V_{GS}	Gate-to-Source Voltage	± 30	V
E_{AS}^{a2}	Single Pulse Avalanche Energy	490	mJ
P_D	Power Dissipation	151	W
T_J, T_{stg}	Operating Junction and Storage Temperature Range	150, -55 to 150	°C
T_L	Maximum Temperature for Soldering	300	°C

Caution: Stresses greater than those listed in the "Absolute Maximum Ratings" may cause permanent damage to the device.

Thermal Characteristics

Symbol	Parameter	Typ.	Units
$R_{\theta JC}$	Junction-to-Case	0.83	°C/W
$R_{\theta JA}$	Junction-to-Ambient	62	°C/W

V_{DSS}	800	V
I_D	20	A
$P_D(T_C=25^\circ\text{C})$	151	W
$R_{DS(ON)TYP}$	0.21	Ω





GL20J80A0

GL Silicon N-Channel Super-Junction Power MOSFET

Electrical Characteristics (Tc= 25°C unless otherwise specified):

OFF Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
V _{DSS}	Drain to Source Breakdown Voltage	V _{GS} =0V, I _D =250μA	800	--	--	V
I _{DSS}	Drain to Source Leakage Current	V _{DS} =800V, V _{GS} =0V, T _a = 25°C	--	--	1.0	μA
		V _{DS} =640V, V _{GS} =0V, T _a =150°C	--	--	250	
I _{GSS(F)}	Gate to Source Forward Leakage	V _{GS} = +30V	--	--	100	nA
I _{GSS(R)}	Gate to Source Reverse Leakage	V _{GS} = -30V	--	--	-100	nA

ON Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
R _{DS(ON)} ^{a3}	Drain-to-Source On-Resistance	V _{GS} =10V, I _D =10A	--	0.21	0.25	Ω
V _{GS(TH)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250μA	2.0	--	3.0	V

Dynamic Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
g _{fs} ^{a3}	Forward Transconductance	V _{DS} =10V, I _D =20A	--	18	--	S
C _{iss}	Input Capacitance	V _{GS} =0V, V _D =25V f=1.0MHz	--	1300	--	pF
C _{oss}	Output Capacitance		--	380	--	
C _{rss}	Reverse Transfer Capacitance		--	22	--	

Resistive Switching Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
t _{d(ON)}	Turn-on Delay Time	V _{DD} =400V, I _D =20A, V _{GS} =10V R _g =25Ω	--	40	--	ns
t _r	Rise Time		--	21	--	
t _{d(OFF)}	Turn-Off Delay Time		--	140	--	
t _f	Fall Time		--	22	--	
Q _g	Total Gate Charge	I _D =40A, V _{DD} =480V V _{GS} =0 to 10V	--	28	--	nC
Q _{gs}	Gate to Source Charge		--	6.5	--	
Q _{gd}	Gate to Drain ("Miller")Charge		--	11	--	



GL20J80A0

GL Silicon N-Channel Super-Junction Power MOSFET

Source-Drain Diode Characteristics

Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
I_S	Continuous Source Current (Body Diode)		--	--	20	A
I_{SM}	Maximum Pulsed Current (Body Diode)		--	--	80	A
V_{SD}	Diode Forward Voltage	$I_S=20A, V_{GS}=0V$	--	--	1.5	V
t_{rr}	Reverse Recovery Time	$I_S=20A, V_{GS}=0V$	--	440	--	ns
Q_{rr}	Reverse Recovery Charge	$I_S=I_F, d_i/d_t=100A/us$	--	5.0	--	uC
Pulse width $t_p \leq 380\mu s, \delta \leq 2\%$						

^{a1}: Repetitive rating; pulse width limited by maximum junction temperature

^{a2}: $I_{AS}=5A, V_{DD}=60V, R_G=25\Omega$, Starting $T_J=25^\circ C$

^{a3}: Pulse Test: Pulse width $\leq 380\mu s$, Duty Cycle $\leq 2\%$

Typical Characteristics

Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current




Figure 4. Capacitance




Figure 5. Gate Charge





Figure 6. Body Diode Forward Voltage



GL Silicon N-Channel Super-Junction Power MOSFET

Figure 7. On-Resistance vs. Junction Temperature





Figure 8. Threshold Voltage vs. Junction Temperature



Max. transient thermal impedance
TO-263

